



LIPPMANN-Milwaukee, Inc. J3048-VGF5120 Portable Diesel Primary Jaw Crushing Plant

Description:

- Lippmann-Milwaukee 30"x48" jaw crusher
 - Manual hydraulic toggle adjustment
- Volvo Diesel Power, TAD942VE, for the jaw main drive
- Twin Disc Clutch, SB314-SP101
- 51" x 20' Vibrating Grizzly Feeder:
 - 15' long pan and 5' grizzly section with bars adjustable from 2.5" – 3.5" nom. openings
 - 40HP Altivar (Square D) AC electric variable speed drive and controls
- 48" x 45' front discharge conveyor with electric drive, qty. 2 * 15HP motors
- Hydraulic leveling jacks, four (4) 70,000 lb., 24" stroke with a 8 hp gas power unit
- The steel truck frame with king-pin (without front dolly) includes:
 - Quad axle Hutch suspension with sixteen (16) Budd type Hub Piloted Wheels
 - 11:00 x 22.5 radial tubeless tires, and air brakes
 - Also includes all necessary chutes and supports, support legs, guards for v-belt drives, operator's platform with railing and ladder, tail lights, reflectors, directional signals, mud flaps and screw jacks
- NEMA 12 Motor Control Center with dust-tight enclosure and full voltage magnetic starters for 40 hp (feeder) and (2) 15 hp (conveyor) motors with:
 - Circuit breaker protection
 - Start/stop push buttons and wiring from the control center to the electric motors (30/60/460 volts)

