



*LIPPMANN-Milwaukee, Inc. J3062-VGF62 18
Portable Primary Jaw Recycling Crushing Plant*

Description:

- Lippmann-Milwaukee 30" x 62" heavy duty jaw crusher
 - With **HYDRAULIC TOGGLE** adjustment
 - Includes an Automatic Oil Lubrication System
- **Volvo Diesel Power**, TAD942VE, for the jaw main drive
 - Twin Disc Clutch, SB314-SP101
- LIPPMANN-Milwaukee Heavy-Duty Horizontal Vibrating Grizzly Feeder
 - **VGF 62" wide and 18' long**
 - 1 1/4" thick steel feeder pan, 14' feet long, with 1/2" thick AR steel liners on pan and 3/8" thick AR liners on side plates of feeder
 - A 4' long grizzly section with adjustable bars and 3-1/2" to 4-1/2" nominal openings (Setting can be adjusted)
 - 40HP Altivar (Square D) AC electric variable speed drive and controls
- The steel truck frame with king-pin (without front dolly) includes:
 - Quad axle Hutch suspension with sixteen (16) Budd type Hub Piloted Wheels.
 - 11:00 x 22.5 radial tubeless tires, and air brakes.
 - Also includes all necessary chutes and supports, support legs, guards for v-belt drives, operator's platform with railing and ladder, tail lights, reflectors, directional signals, and mud flaps.
- The plant has a by-pass chute under the grizzly section of the feeder.
- **Hydraulic leveling jacks**, four (4) 70,000 lb., 36" stroke with a 8 hp gas power unit
- **Motor Control Center panel** with dust-tight enclosure and full voltage magnetic starters with:
 - Circuit breaker protection
 - Start/stop push buttons and wiring from the control center to the electric motors (30/60/460 volts)

